

## **Technical Data Sheet**

### **RXM Texture Coat**

The RXM Texture coat is a durable and decorative interior acrylic latex coating. The texture coat can be applied to drywall, plaster, wood, cement block, masonite, tile and metal. Note: rough surfaces may need to be primed and skim coated to achieve a smooth surface before the application of the RXM texture coat. RXM Texture coat is formulated using modern acrylic chemistry and contains no clay, plaster, or cement compounds. It remains flexible when cured making it resistant to cracking.

### **RECOMMENDED USES**

RXM Texture coat is a spray applied coating for interior walls or ceilings. This coating is designed to replace paint or wallpaper.

### **PRODUCT FEATURES**

- Pleasing flat textured finish
- Excellent moisture resistance
- Excellent filling characteristics
- Resists cracking chipping and peeling
- High hiding and excellent adhesion
- Excellent color retention
- Durable finish
- Resists mold and mildew
- Easy to apply
- Virtually odor free and water based
- Non-flammable
- Soap and water cleanup
- Laboratory tested
- Made in the USA
- Non-photo chemically reactive

### **SURFACE PREPARATION**

Surfaces to be coated must be clean dry and free of wax, grease, dust, mildew, water soluble materials, and scaling paint. Glossy areas should be dulled. New plaster or masonry surfaces must be allowed to cure (30-60days) before coating. All masonry surfaces must be thoroughly brushed with stiff fiber bristles to remove loose particles. TM Pratt offers a number of specialty primers for use over difficult substrates such as bleeding woods, hard glossy surfaces, galvanized metal, or other substrates where paint adhesion or stain suppression is a particular problem. Contact the company for options.

### **PRIMER/FINISH SYSTEMS**

Depending on substrate conditions and finish look desired, there are many options. See the company's installation manual or marketing materials for more details.

### **APPLICATION**

RXM Texture coat is installed by commercial painting contractors that have been trained in the application of the company's products. The application of the RXM Texture coat must be done as described in the company's printed installation manual.

### **COVERAGE**

50-100 square feet per gallon. Depending on previous color, surface porosity, and texture coverage can vary greatly. Coverage is also varied by the desired texture look. See the installation manual for details or contact the company for more information.

## TECHNICAL DATA

Finish:	Flat Textured
Color:	White or custom tinted to match any paint color
Vehicle Type:	Proprietary blend of acrylic latexes
Pigment type:	Titanium Dioxide
Dries by:	evaporation, coalescence
Viscosity:	mastic
Weight per gallon:	14.4 pounds
Specific Gravity:	1.72
Weight Solids:	73.6%
Volume Solids:	54.7%
% vehicle by weight:	35.6%
% vehicle by volume:	58.9%
% pigment by weight:	63.2%
% pigment by volume:	39.2%
% solvent by weight:	26.4%
% solvent by volume:	45.3%
% vehicle solids by weight:	9.3%
% vehicle solids by volume:	13.6%
Theoretical coverage at recommended film thickness of 50-100 sf/g	
Wet film thickness:	16.0 – 32.1 mils
Dry film thickness:	8.7 – 17.6 mils
60° specular gloss:	flat
Surface application temperature:	min 50° F max 90° F
Clean up with:	clean water
Flash point (seta):	none
V.O.C. Material:	9g/l; .07 lb/gal
V.O.C. Coating:	16g/l; .13lb/gal

## DRYING TIME

Dry Time@ 77°F (25C) @50% RH

Set to touch 12 hours

To recoat: 24 hours

To service: 24-48 hours

Drying times may vary based on temperature, humidity, air movement, and application techniques.

## THINNING /CLEANUP

Thinning is unnecessary and may affect color. If necessary to achieve application properties thinning may be done with a small amount of clean water. Never thin with other paints or solvents. Clean hands, tools, and equipment with warm soapy water. Spray equipment should be given a final rinse with mineral spirits to prevent rusting. USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state designated environmental agency for information on disposal options.

## CERTIFICATION

Formulated without lead, mercury, or chromates.

## LIMITATIONS

Do not apply when air and surface temperatures are below 50 (10C)

## **STORAGE**

Twelve month shelf life if containers are sealed, stored upright, and stored in a dry place. Maintain temperatures between 45° F and 100° F. If skins form on the surface during storage, they must be removed before moving, mixing, or using.

## **TECHNICAL ASSISTANCE**

For further assistance contact TM Pratt & Company, Inc.

## **MAINTENANCE**

Avoid washing for 7 days. Once cured, dirt and stains can be removed with a mild (non-abrasive, non-chlorine) detergent mixed with water. RXM Texture coat can be repaired by property personnel (on-site training and repair kits are provided by TM Pratt).

## **PRODUCT AVAILABILITY**

Available in five gallon containers weighing 72.7 pounds. RXM Texture coat can be factory tinted to match virtually any paint color.

## **ENVIRONMENTAL/SAFETY**

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application and sanding. A dust/particulate respirator approved by NIOSH should be worn during application or sanding. Close containers after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek immediate medical attention.

**IN CASE OF SPILL:** Absorb with inert material and dispose of as specified under THINING/CLEANUP above.

Hazardous Materials Identification System @ NPCA

Health:-1

Flammability- 0

Reactivity – 0

Personal protection-

0= Minimal 4= Severe Hazard

Material safety data sheets are available at [www.tmpratt.com](http://www.tmpratt.com) or contact the company

## **CAUTION**

**KEEP OUT OF REACH OF CHILDREN Ⓢ PROTECT FROM FREEZING Ⓢ DO NOT TAKE INTERNALLY**

## **LIMITED WARRANTY**

In lieu of all other warranties or guarantees, express or implied by contract or law, manufacturer's liability is hereby limited to replacement of such quantities of this material if found to be defective. Manufacturer shall not be liable for any representation, warranties, (express or implied) made by any of its agents, representatives, or employees or by any applicator regarded the RXM Texture Coat. In no case will manufacturer reimburse for extra labor cost or be responsible for damage or replacement of substrates to which this product is applied. Contact company for a complete description of its limited warranty.